Part#FVKSKIT: Fireview 205 Load Door Gasket Kit Rev. Date 7/26/2021

Parts Needed:

(4') 3/8" LD Graphite rope gasket

(1) Bottle gasket glue

Tools Needed:
Putty knife
Scissors
7/16 Wrench
1/8" Allen wrench
WD-40, Kroil, PB Blaster, or similar
penetrating liquid



- 1. Make sure the stove is cool. You will need 4' of .375" LD graphite gasket and gasket glue.
- 2. Open the loading door. Pull straight up on the door. The hinge pins should slide up and out of the hinges in the doorframe. It may be helpful to swing the door back and forth as you lift.



3. Lay the door face down on a suitable work surface. Use a putty knife or flat-head screwdriver to remove the old gasket. A wire brush can be used to clean out glue and old gasket residue from the gasket channel. Vacuum any leftover debris from the door and gasket channel.

Email: <u>info@woodstove.com</u>
Web: www.woodstove.com



- 4. Apply a 3/16" bead of glue around the prepared channel.
- 5. Start at the bottom center of the door with one end of the gasket and press it into the channel. Push gasket back slightly as you round the corners to ensure full coverage. Use a putty knife to tuck the gasket in place if necessary. Do not stretch or compress the gasket as you work it around the door. Use sharp scissors to cut the gasket to the proper length and tuck end in.





6. Return the door to the stove. Align the hinge pins with the hinges on the doorframe. As you press down on the pins it may be helpful to swing the door back and forth until it is all the way down on the hinges. Apply lubricant if needed.



7. Close and open the door firmly several times to seat the gasket. If necessary, adjust the set screw on the door latch for the proper tension. Use a 7/16° wrench to loosen the lock nut and a 1/8° Allen wrench to turn the set screw.



8. Allow the heat safe gasket glue to cure for at least 30 minutes before using the stove.

We need your help! Woodstock Soapstone Co. takes great pride in providing the highest quality products as well as the best customer service in our industry. We welcome your suggestions and input to help us achieve these goals. If you have any comments to improve our products, service, and information provided in these instructions please contact us at (800) 866-4344 or info@woodstove.com. Thank you.