

## Absolute Steel Top Lid Replacement

Please read all the instructions before you begin the procedure. Confirm that you have all the necessary tools and materials. If you have any questions, technical support is available toll free at 1-800-866-4344, Monday-Saturday 9:00 – 5:00 ET

### **Tools Needed:**

- 7/16" wrench or socket
- 5/32 allen wrench

1. Open the top lid of the stove and lift it straight up and off. Place the lid upside down on a bench.



2. Using a 7/16" wrench or socket, remove the 6 hex nuts from the bolts. Lift the heat shield straight up to remove. Then remove the 6 heat shield spacers and set the shield, the nuts, and spacers aside.



3. Carefully lift the lid straight up, leaving behind the artwork and the flat head bolts.



4. Carefully position the new lid over the screws and drop it down. Replace the 6 spacers and the heat shield. Start all 6 six nuts by hand. You should be able to tighten them sufficiently with the 7/16" wrench. If not, stand the lid on edge so you can use the 5/32" allen wrench to keep the flat head bolts stationary while you tighten all the nuts.
5. Return the lid to the stove.

**We need your help!** Woodstock Soapstone Co. takes pride in providing the highest quality products as well as the best customer service in our industry. We welcome your suggestions and input to help us achieve these goals. If you have any comments to improve our products, service, and information provided in these instructions please contact us at (800) 866-4344 or [info@woodstove.com](mailto:info@woodstove.com). Thank you.

Revised 4/30/19